

## SAMPLE INSPECTION AND MAINTENANCE LOG

The sample log suggests records that should be maintained by the purchaser or the rescue equipment user.

| Equipment Inspection and Maintenance Log |                        |                       |      |
|--|------------------------|-----------------------|------|
| Item _____ # _____                       |                        | Date in Service _____ |      |
| Brand/Model _____                        |                        | Strength _____        |      |
| Date                                     | How Used or Maintained | Comments              | Name |
|  |                        |                       |      |
|  |                        |                       |      |
|  |                        |                       |      |

### WARNING

- **Serious injury or death may result from the improper use of this equipment.**
- **This equipment has been designed and manufactured for use by experienced professionals only.**
- **Do not attempt to use this equipment without proper training.**

### CMC Rescue, Inc.

P. O. Box 6870, Santa Barbara, CA 93160  
USA

805-562-9120

www.cmcrescue.com

**ISO 9001 : 2000 Certified**

© 2003, CMC Rescue, Inc., Control No. 20160X.00.010407

### USER INSTRUCTIONS

NFPA Standard 1983 recommends separating the user instructions from the Utility Strap and retaining them in a permanent record. The standard also recommends making a copy of the instructions to keep with the Utility Strap and that the instructions should be referred to before and after each use.

Additional information regarding life safety auxiliary equipment can be found at least in the NFPA 1500, *Standard on Fire Department Occupational Safety and Health Program*, and NFPA 1983, *Standard on Life Safety Rope and Equipment for Emergency Services*.

### INSPECT AFTER EACH USE

Inspect the Utility Strap according to your department's policy for inspecting rescue equipment. The Utility Strap should be inspected after each use by an inspector that meets your department's training standard for inspection of rescue equipment. Record the date of the inspection and the results in the equipment log or on a tag that attaches to the Utility Strap. Each user should be trained in equipment inspection and should do a cursory inspection before each use.

When inspecting the Utility Strap, check the webbing for cuts, worn or frayed areas, broken fibers, soft or hard spots, discoloration, or melted fibers. Check the stitching for pulled threads, abrasions, or breaks. Check the hardware for damage, sharp edges, and improper operation. If any of the above are noted, or if the Utility Strap has been subjected to shock loads, fall loads, or abuse other than normal use, remove it from service and destroy it. If there is any doubt about the serviceability of the Utility Strap, remove it from service and destroy it.

## IMPORTANT INSTRUCTIONS - PLEASE READ AND SAVE



# Roco Utility Strap

Made in USA

of US and foreign components

## PRODUCT LABEL

- **USE ONLY IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.**
- **INSPECT AFTER EACH USE IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.**
- **REPAIR ONLY IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.**



5F04

THIS RIGGING STRAP MEETS THE AUXILIARY EQUIPMENT REQUIREMENTS OF NFPA 1983, STANDARD ON LIFE SAFETY ROPE AND EQUIPMENT FOR EMERGENCY SERVICES, 2006 EDITION.


EMERGENCY SERVICES AUXILIARY EQUIPMENT. IN ACCORDANCE WITH THE NATIONAL FIRE PROTECTION ASSOCIATION STANDARD ON LIFE SAFETY ROPE AND EQUIPMENT FOR EMERGENCY SERVICES.

- Rated for General Use (G)
- MBS 45 kN (10,120 lbf)


### USING YOUR UTILITY STRAP

The Utility Strap can be used in the following configurations:

1. Doubled so that the bend in the webbing is around the anchor. The two D-ring ends are then brought together side by side to form a single connection point. This configuration has a MBS of 45 kN.



2. By passing the end with the small D-Ring through the end with the large D-Ring, the strap can be rigged as a choker around the anchorage forming a single connection point. This configuration has a MBS of 26 kN.



**WARNING: Take caution when using the strap around an anchor when one carabiner is clipped to both D-Rings. The carabiner may rotate so that the load is on the gate. Check the carabiner and if necessary adjust the strap and carabiner to avoid tri-axial loading or cross loading of the carabiner.**

### MAINTENANCE

If the Utility Strap becomes soiled, it can be washed in cold water with a mild detergent. Roco recommends the use of CMC LIFELINE Cleaner. Dry out of direct sunlight. Do not dry in an automatic dryer. Do not expose the strap to flame or high temperature. Store and carry the strap where it will be protected as it could melt or burn and fail if exposed to flame or high temperature

### REPAIR

Roco recommends that all repair work be done by the manufacturer. All other repair work or modifications may void the warranty and shall release Roco Rescue, Inc. and its manufacturer, CMC Rescue, Inc., from all liability and responsibility as the manufacturer.